

SIKORA XXXXX PURITY CONCEPT XX

XXXXXXXXXX/XXXXXXXXXX

XXXXXXXXXXXXXXXXXX

XXXXXXXXXXPURITY CONCEPT XXXXXX?XX50 µmXXXXXXXXXXPURITY CONCEPT XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

XXXX

XXXX *	PURITY CONCEPT X: X XXXX PURITY CONCEPT V: ??CMOSXXXXXXXXXX
XXXX	XXXXXXXXXX/XXXXXXXXXXXX
XXXXXX	PURITY CONCEPT X: XXXXX XXXXXXXXXXXXXXX PURITY CONCEPT V: XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXX	X XXXXX 50 µm (??? 3D), 50 x 50 x 50 µm XXXXX 50 µm (?? 2D), 50 x 50 µm
XXXXXXXXXX	+10 – + 40 °C
XXXX	USB ??LAN
XXXX	PURITY CONCEPT X: 230 V AC (alternativ 100 V AC oder 115 V AC) ± 10%, 50/60 Hz PURITY CONCEPT V: 100 - 240 V AC ± 10 %, 50/60 Hz
XXXX	PURITY CONCEPT X: 1,309 x 831 x 1,882 mm PURITY CONCEPT V: 1,090 x 575 x 921 mm (?? x ?? x ??)

PURITY CONCEPT X ?X XXXXX

PURITY CONCEPT X ??? X XX

PURITY CONCEPT V XXXXXX

PURITY CONCEPT V XX

XXXX

- XXXXXXXXXXXXX
- XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX/XXXXXX
- XXXX
- XXXXXXXXX

XXXX

X-ray scanner for pellet, flakes and film inspection and analysis